



4 wheel steer reduces crop damage on headland turns

### Spraying Made Easy



- **Genius Electronics**
- CanBus data transmitted by 1 single cable
- GPS or wheel sensor speed control
- Precision rate control
- Multi-data information screen, speed, rate
- 100 field memories
- Integral sequential switching up to 20 sections
- **Commando Electronics**
- CanBus electro-hydraulic controls
- **Options:-**
- Headland assist
- Electronic tank contents
- Gemini electronic read-out at fill station
- Tank fill audible warning
- SpraySat auto multi-section switching
- USB downloading port
- Variable rate control
- Guidance screen

# Landquip Stretched Fastrac



3000, 3500 or 4000 litres  
18 to 38 metre **Alu-light** Booms  
Best weight distribution available



**Landquip**

METFIELD ROAD, FRESSINGFIELD, SUFFOLK, IP21 5SD, UK

Tel:- 44 (0)1379 588286 Fax:- 44 (0)1379 588292

E-mail:- [sales@landquip.co.uk](mailto:sales@landquip.co.uk) [www.landquip.co.uk](http://www.landquip.co.uk)

**Landquip** demounts offer the very best weight distribution of any demount available for the Fastrac. The spray pump and chemical bowl are fitted to the sprayer chassis, making demounting possible in 10 minutes.

**Landquip** demounts are fitted with **Alu-light** booms, offering their well-proven and accepted features experienced by farmers for more than 20 years. These booms give an incredible in-field performance due to their levelling system that complements the Fastrac's unique suspension, allowing accurate performance at speeds up to 20 kph.

### **Booms**

Tried and tested **Alu-light** booms (up to 38 metres) equipped with stainless steel spray lines with **Poziflow** continuous recirculation and air on/off.

Multi-head 360° nozzle bodies carry up to 5 ceramic, high pressure, low drift tips - or Umbrella fertiliser jets.



### Standard equipment includes:

- Low centre of gravity high capacity tank
- 300 litre flushing tank - 15 litre handwash
- Chemical-less sight tube
- 6 cylinder 300 l/min pump
- Electro-hydraulics requiring only 1 spool valve
- Stainless steel spraylines - Line filters
- Multi-head nozzle bodies with ceramic tips
- Rear mudguards
- Stainless steel chemical bowl
- Demount legs

A strategically mounted 700 litre hydraulically driven pump enables easy access to the 800 litre capacity filter for cleaning, and gives full access to the drawbar for bowser towing

### **Spray Pumps**

PTO driven 300 l/min 6 cylinder piston diaphragm  
Or  
Hydraulically driven 700 l/min high pressure, self priming centrifugal