

Landquip



Trailblazer Sprayers

6000 ltr Trailblazer sprayer fitted with
36 metre TR5 Alu-light contractors' boom



CANBUS ELECTRONIC RATE CONTROL

FULL ELECTRONIC AUTO STEERING

AIRIDE SUSPENSION

24 - 40m ALU-LIGHT BOOMS

PATENTED HYDRAULIC ANTI-YAW PROTECTION

5000 - 7000 ltr TANKS

POZIFLOW RECIRCULATION

The well-proven Alu-light booms have characteristics which give them very low destructive forces compared with their steel equivalents. Tracking systems exaggerate these forces making the boom design on this type of sprayer of paramount importance. Alu-light booms can be successfully used on **Trailblazer** sprayers up to 40 metre widths whilst retaining strength and reliability at spraying speeds up to 16 kph.

The one-piece chassis design together with unique main tank shape enables the steering axle to achieve tight in-field turns. Controlled by an electronic auto tracking device, the heavy duty axle follows the tractor wheelings. The system gives very good machine stability enabling large tank capacities and complements wide boom performance.

The **Trailblazer** has a pneumatic level ride axle suspension system that gives a smooth performance in or out of the field.

High output hydraulically driven centrifugal pumps enable a 40 metre machine to apply up to 600 litres/hectare at 12 kph obtaining spot work rates of 57 hectares (130 acres)/hour. Whilst the **Trailblazer** is ideally suited to high volume liquid fertiliser applications, it is equally at home spraying low volumes and high pressures up to 10 bar through air inclusion ceramic jets.

Equipped with large 1.9m diameter, 6.0m circumference easy-to-pull flotation or row crop wheels, the **Trailblazer** is suited to tractors in the region of 120+ hp.



Pneumatic level ride load sensing air suspension axle

Unsurpassed in-field boom performance plus excellent stability and ride at high road speed

Alu-light Booms 24 to 40m

Engineered to a high standard in aluminium
Trapezium self levelling
'Gull-wing' folding for safety
Three-way auto reset break-backs
Resistant to liquid fertiliser
Hydraulic tilt standard
Variable geometry on 30m+

Landquip

METFIELD ROAD, FRESSINGFIELD, SUFFOLK, IP21 5SD, UK.

TEL: 44 (0)1379 588286

FAX: 44 (0)1379 588292

E-mail: sales@landquip.co.uk

Web: www.landquip.co.uk