



**Fastrac 4220 equipped with 24 metre bi-fold aluminium boom + Vision 1500 front tank = total capacity 4000 litres (4400 litres with Vision 1900)**



#### **Bravo Electronics - Spraying made easy**

- New high resolution 5.7" display
- CanBus data transmitted by 1 single cable
- Precision rate control
- CanBus electro-hydraulic controls
- GPS sensed speed
- Manual sequential switching of up to 13 sections
- GPS automatic shut-off of each individual nozzle
- Automatic on-the-move selection of appropriate nozzle according to speed, spray rate & pressure
- Built in LED lightbar guidance system
- USB job export in Shape format



- 2GB internal memory to store jobs
- 2 camera inputs/ports
- Options:-
- Delta 80 8.4" display
- Headland nozzle switching
- In-fill sensor
- Tank contents
- In-fill electronic read-out at fill station
- Variable rate control
- Boom levelling
- Joystick controls
- IsoBus controls

E & O E

**Landquipp**

FRESSINGFIELD, SUFFOLK, IP21 5SD, UK

Tel:- 44 (0)1379 588286  
E-mail:- [sales@landquipp.co.uk](mailto:sales@landquipp.co.uk)  
Web:- [www.landquipp.co.uk](http://www.landquipp.co.uk)

Using your smartphone, scan code to link direct



# Landquipp Fastrac Sprayers



**2000 or 2500 litres**  
**18 to 24m Bi-fold, 30 to 36m Tri-fold Alu-light Booms**  
**Best weight distribution available**  
**Rear fold booms - 18, 20, 24, 28 & 30 metre widths**





## Fastrac 4000 series Demount Sprayer Range



### Booms

Tried and tested Alu-light booms (up to 36 metres) equipped with stainless steel spray lines with Poziflow continuous recirculation

Multi-head 360° nozzle bodies carry up to 5 ceramic, high pressure, low drift tips  
- or Umbrella fertiliser jets

Fully approved by JCB, **Landquip** demounts offer the very best weight distribution of any demount available for the Fastrac. The spray pump and chemical bowl are fitted to the sprayer chassis, making demounting possible in 10 minutes.

**Landquip** demounts are fitted with Alu-light booms, offering their well-proven and accepted features experienced by farmers for more than 30 years. These booms give an incredible in-field performance due to their levelling system that complements the Fastrac's unique suspension, allowing accurate spraying at speeds up to 25 kph.



### Standard equipment includes:

- Low centre of gravity fibreglass tank
- 200 litre flushing tank - 15 litre handwash
- Chemical-less sight tube
- Electro-hydraulics requiring only 1 spool valve
- Stainless steel spraylines - Pressure filters
- Multi-head nozzle bodies with ceramic tips
- Rear mudguards
- 30 litre easy clean chemical bowl
- Demount legs
- **Option:-**
- Boom line air blow out system for easy washing using less water



A strategically mounted hydraulically driven pump enables easy access to the 800 litre capacity filter for cleaning, and gives full access to the drawbar for bowser towing (on gull-wing folding models only)

### Spray Pumps

PTO driven 330 or 450 l/min radial piston diaphragm



Fill station with 30 litre easy-clean chemical bowl mounted on nearside with all taps within easy reach  
←  
*Optional suction probe*



Low centre pivot / trapezium boom levelling system with hydraulic tilt, variable geometry and hydraulic anti-yaw